



Interrupteurs différentiels

Bipolaires










10 MA **30 MA** **300 MA**

- Protection différentielle
- Bornes alignées 25 mm²
- In de 16 A à 100 A
- Un 230 V ~ 50/60 Hz
- Type A - AC - G
- I_{Δn} 10, 30 et 300 mA
- I_{Δc} 10000 A
- Norme EN 61008-1

 **Fiche technique**
téléchargeable sur le site



* Voir les références concernées

	Calibre	Type AC 	Type A 	Type G 	Module	Emballage
10 mA	16 A	03492	-	-	2	1
30 mA	40 A	03412 	03422 	03426	2	1
	63 A	03414 	03424 	03428	2	1
	80 A	03416	-	-	2	1
	100 A	03418	-	-	2	1
300 mA	40 A	03452	-	-	2	1
	63 A	03454	-	-	2	1
	80 A	03456	-	-	2	1
	100 A	03458	-	-	2	1

ACCESSOIRES



06032



06018



06016

Référence	Description	Emballage
06032	Peigne d'alimentation verticale 63 A ID/ID	1
06018	Kit d'alimentation 63 A ID2/5DPN 7 modules	1
06016	Kit d'alimentation 63 A ID2/11DPN 13 modules	1
06112	Peigne bipolaire 63 A 1 mètre	1
06122	Peigne bipolaire 63 A à fourche 1 mètre	1