



Disjoncteurs bipolaires


6000 A 10 000 A

- > Protection magnétothermique
- > Bornes alignées 25 mm²
- > In 10 à 63 A
- > 230/400 V 50/60 Hz
- > Classe 3
- > Courbe de déclenchement B*, C et D
- > Pdc 6000 A & 10000A sous 380... 400 Vac
- > Norme IEC/EN 60898-1



i Association

Modules auxiliaires (Mx, OF, Sd) P.56

Blocs différentiels P.55

CALIBRE	6 KA		10 KA	MODULE	EMBALLAGE
	COURBE C	COURBE D	COURBE C		
10 A	02010	02066	02122	2	6
16 A	02012	02068	02124	2	6
20 A	02014	02070	02126	2	6
25 A	02016	02072	02128	2	6
32 A	02018	02074	02130	2	6
40 A	02020	02076	02132	2	6
50A	02022	02078	02134	2	6
63 A	02024	02080	02136	2	6

* Courbe B sur demande

ACCESSOIRES



06005



06112



06010



06008

RÉFÉRENCE	DESCRIPTION	NOMBRE DE PÔLES	EMBALLAGE
06112	Peigne bipolaire 63 A	54	1 m
06122	Peigne bipolaire 63 A à fourche	54	1 m
06010	Connecteur 25 mm ²	-	20
06008	Connecteur 25 mm ² à fourche	-	20